10频合路器技术规格书 -

KXT-FF-02 · 誊自清工厂 Word 原稿

下表按原稿誊清。整列与前一列完全相同的合并格已去掉。页末点名的笔误已改正，其余数字没有改写。

端口 1

项目	原稿指标
端口	1
频率范围	791-821
插入损耗	≤2.0
驻波比	≤1.3
带内波动	≤1.8
带外抑制（dB）	≥80@832 ≥80@880 ≥80@925 ≥80@1710 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率	≥20W
工作温度(℃)	-30～+60
接口形式	N-K/SMA-F
外观	本色

端口 2

项目	原稿指标
端口	2
频率范围	832-862
插入损耗	≤2.0
带内波动	≤1.8
带外抑制（dB）	≥80@821 ≥80@880 ≥80@925 ≥80@1710 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率	≥20W †
工作温度(℃)	-30～+60 †
接口形式	N-K/SMA-F †
外观	本色 †

端口 3

项目	原稿指标
端口	3
频率范围	880-915
插入损耗	≤2.0
带内波动	≤1.8
带外抑制（dB）	≥80@821 ≥80@862 ≥80@925 ≥80@1710 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率	≥20W †
工作温度(℃)	-30～+60 †
接口形式	N-K/SMA-F †
外观	本色 †

端口 4

项目	原稿指标
端口	4
频率范围	925-960
插入损耗	≤2.0
带内波动	≤1.8
带外抑制（dB）	≥80@862 ≥80@821 ≥80@915 ≥80@1710 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620

平均功率	≥20W †
工作温度(℃)	-30～+60 †
接口形式	N-K/SMA-F †
外观	本色 †

端口 5

项目	原稿指标
端口	5
频率范围	1710-1785
插入损耗	≤2.0
带内波动	≤1.8
带外抑制（dB）	≥80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率	≥20W †
工作温度(℃)	-30～+60 †
接口形式	N-K/SMA-F †
外观	本色 †

端口 6

项目	原稿指标
端口	6
频率范围	1805-1880
插入损耗	≤2.0
带内波动	≤1.8
带外抑制（dB）	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1785 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率	≥20W †
工作温度(℃)	-30～+60 †
接口形式	N-K/SMA-F †
外观	本色 †

端口 7

项目	原稿指标
端口	7
频率范围	1920-1980
插入损耗	≤2.0
带内波动	≤1.8
带外抑制（dB）	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1880 ≥80@1785 ≥80@2110 ≥80@2500 ≥80@2620
平均功率	≥20W †
工作温度(℃)	-30～+60 †
接口形式	N-K/SMA-F †
外观	本色 †

端口 8

项目	原稿指标
端口	8
频率范围	2110-2170
插入损耗	≤2.0
带内波动	≤1.8
带外抑制（dB）	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1805 ≥80@1920 ≥80@1785 ≥80@2500 ≥80@2620
平均功率	≥20W †

工作温度(℃)	-30 ~ +60 †
接口形式	N-K/SMA-F †
外观	本色 †

端口 9

项目	原稿指标
端口	9
频率范围	2500-2570
插入损耗	≤2.0
带内波动	≤1.8
带外抑制（dB）	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@1785 ≥80@2620
平均功率	≥20W †
工作温度(℃)	-30 ~ +60 †
接口形式	N-K/SMA-F †
外观	本色 †

端口 10

项目	原稿指标
端口	10
频率范围	2620-2690
插入损耗	≤2.0
带内波动	≤1.8
带外抑制（dB）	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@1785
平均功率	≥20W †
工作温度(℃)	-30 ~ +60 †
接口形式	N-K/SMA-F †
外观	本色 †

说明

· 来源文件：10频合路器技术规格书 -.doc
· 特性阻抗：原稿写了 50 Ω 的，以原稿为准；原稿没写的，N 与 SMA 口按 50 Ω。
· 室内型铝合金腔体。测试条件 25 °C、50 Ω、矢量网络分析仪。出货附该件测试报告。
· 原稿没有互调指标。若订单选择低互调档，按 PIM3 ≤ −150 dBc @ 2×43 dBm 测试并写入报告。
· 多端口表：插损、抑制、隔离只印该端口原稿里有的格子。标 † 的是合并单元格，字只出现在部分端口，已抄到空白端口，数字未改。

English

Factory specification

KXT-FF-02 · 10频合路器技术规格书 -

Transcribed from the factory Word file. A column is omitted only when it duplicates the previous column in every row. Typos named in the notes are corrected. Every other number is unchanged.

Port 1

Item	As written
端口	1
频率范围 / Frequency	791-821
插入损耗 / Insertion loss	≤2.0
驻波比 / VSWR	≤1.3
带内波动 / Ripple	≤1.8
带外抑制（dB） / Rejection	≥80@832 ≥80@880 ≥80@925 ≥80@1710 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率 / Average power	≥20W
工作温度(℃) / Operating temperature	-30 ~ +60
接口形式 / Connector	N-K/SMA-F
外观 / Finish	本色

Port 2

Item	As written
端口	2
频率范围 / Frequency	832-862
插入损耗 / Insertion loss	≤2.0
带内波动 / Ripple	≤1.8
带外抑制（dB） / Rejection	≥80@821 ≥80@880 ≥80@925 ≥80@1710 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率 / Average power	≥20W †
工作温度(℃) / Operating temperature	-30 ~ +60 †
接口形式 / Connector	N-K/SMA-F †
外观 / Finish	本色 †

Port 3

Item	As written
端口	3
频率范围 / Frequency	880-915
插入损耗 / Insertion loss	≤2.0
带内波动 / Ripple	≤1.8
带外抑制（dB） / Rejection	≥80@821 ≥80@862 ≥80@925 ≥80@1710 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率 / Average power	≥20W †
工作温度(℃) / Operating temperature	-30 ~ +60 †
接口形式 / Connector	N-K/SMA-F †
外观 / Finish	本色 †

Port 4

Item	As written
端口	4
频率范围 / Frequency	925-960
插入损耗 / Insertion loss	≤2.0
带内波动 / Ripple	≤1.8

带外抑制（dB） / Rejection	≥80@862 ≥80@821 ≥80@915 ≥80@1710 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率 / Average power	≥20W †
工作温度(℃) / Operating temperature	-30 ~ +60 †
接口形式 / Connector	N-K/SMA-F †
外观 / Finish	本色 †

Port 5

Item	As written
端口	5
频率范围 / Frequency	1710-1785
插入损耗 / Insertion loss	≤2.0
带内波动 / Ripple	≤1.8
带外抑制（dB） / Rejection	≥80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率 / Average power	≥20W †
工作温度(℃) / Operating temperature	-30 ~ +60 †
接口形式 / Connector	N-K/SMA-F †
外观 / Finish	本色 †

Port 6

Item	As written
端口	6
频率范围 / Frequency	1805-1880
插入损耗 / Insertion loss	≤2.0
带内波动 / Ripple	≤1.8
带外抑制（dB） / Rejection	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1785 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@2620
平均功率 / Average power	≥20W †
工作温度(℃) / Operating temperature	-30 ~ +60 †
接口形式 / Connector	N-K/SMA-F †
外观 / Finish	本色 †

Port 7

Item	As written
端口	7
频率范围 / Frequency	1920-1980
插入损耗 / Insertion loss	≤2.0
带内波动 / Ripple	≤1.8
带外抑制（dB） / Rejection	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1880 ≥80@1785 ≥80@2110 ≥80@2500 ≥80@2620
平均功率 / Average power	≥20W †
工作温度(℃) / Operating temperature	-30 ~ +60 †
接口形式 / Connector	N-K/SMA-F †
外观 / Finish	本色 †

Port 8

Item	As written
端口	8
频率范围 / Frequency	2110-2170
插入损耗 / Insertion loss	≤2.0
带内波动 / Ripple	≤1.8

带外抑制（dB） / Rejection	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1805 ≥80@1920 ≥80@1785 ≥80@2500 ≥80@2620
平均功率 / Average power	≥20W †
工作温度(℃) / Operating temperature	-30 ~ +60 †
接口形式 / Connector	N-K/SMA-F †
外观 / Finish	本色 †

Port 9

Item	As written
端口	9
频率范围 / Frequency	2500-2570
插入损耗 / Insertion loss	≤2.0
带内波动 / Ripple	≤1.8
带外抑制（dB） / Rejection	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@1785 ≥80@2620
平均功率 / Average power	≥20W †
工作温度(℃) / Operating temperature	-30 ~ +60 †
接口形式 / Connector	N-K/SMA-F †
外观 / Finish	本色 †

Port 10

Item	As written
端口	10
频率范围 / Frequency	2620-2690
插入损耗 / Insertion loss	≤2.0
带内波动 / Ripple	≤1.8
带外抑制（dB） / Rejection	80@862 ≥80@915 ≥80@960 ≥80@821 ≥80@1805 ≥80@1920 ≥80@2110 ≥80@2500 ≥80@1785
平均功率 / Average power	≥20W †
工作温度(℃) / Operating temperature	-30 ~ +60 †
接口形式 / Connector	N-K/SMA-F †
外观 / Finish	本色 †

Notes

· Source file: 10频合路器技术规格书 -.doc
· Impedance: where the source states 50 Ω, that stands. Where it is silent, N and SMA ports are 50 Ω.
· Indoor aluminum cavity. Tested at 25 °C in a 50 Ω system on a vector network analyzer. A test report ships with the unit.
· The source sheet has no PIM limit. If the order selects the low-PIM option, test PIM3 to ≤ −150 dBc @ 2×43 dBm and put it on the report.
· Multi-port sheet: insertion loss, rejection and isolation are printed only where that port’ s source cell has text. A cell marked † repeats a merged source cell onto a blank port. The number is unchanged.