修改-8改7频合路器技术规格书（B1、B3、B40、B41、N78）2

KXT-FF-28 · 誊自清工厂 Word 原稿

下表按原稿誊清。整列与前一列完全相同的合并格已去掉。页末点名的笔误已改正，其余数字没有改写。

端口 1

项目	原稿指标
端口	1
频率范围(MHz)	1710-1785
插入损耗(dB)	≤3.0
驻波比	≤1.3
带内波动（dB）	≤2.5
带外抑制（dB）	90@3300-3800 90@2500-2570 90@1805-1880 90@1920-1980 90@2110-2170 90@2300-2400 90@2620-2690
平均功率容量(W)	≥100W †
工作温度(℃)	-30～+60
工作湿度（%）	5～95
接口形式	DIN/ SMA-F
外观	黑色油漆
外形尺寸	362*208*35.5

端口 2

项目	原稿指标
端口	2
频率范围(MHz)	1805-1880
插入损耗(dB)	≤2.0
带内波动（dB）	≤1.8
带外抑制（dB）	90@3300-3800 90@1710-1785 90@2500-2570 90@1920-1980 90@2110-2170 90@2300-2400 90@22620-2690
平均功率容量(W)	≥100W
工作温度(℃)	-30～+60 †
工作湿度（%）	5～95 †
接口形式	DIN/ SMA-F †
外观	黑色油漆 †
外形尺寸	362*208*35.5 †

端口 3

项目	原稿指标
端口	3
频率范围(MHz)	1920-1980
插入损耗(dB)	≤3.0
带内波动（dB）	≤2.5
带外抑制（dB）	90@1710-1785 90@2500-2570 90@1805-1880 90@3300-3800 90@2110-2170 90@2300-2400 90@2620-2690
平均功率容量(W)	≥100W †
工作温度(℃)	-30～+60 †
工作湿度（%）	5～95 †
接口形式	DIN/ SMA-F †
外观	黑色油漆 †
外形尺寸	362*208*35.5 †

端口 4

项目	原稿指标

端口	4
频率范围(MHz)	2110-2170
插入损耗(dB)	≤2.0
带内波动（dB)	≤1.8
带外抑制（dB)	90@1710-1785 90@2500-2570 90@1805-1880 90@3300-3800 90@1920-1980 90@2300-2400 90@2620-2690
平均功率容量(W)	≥100W
工作温度(℃)	-30～+60 †
工作湿度（%)	5～95 †
接口形式	DIN/ SMA-F †
外观	黑色油漆 †
外形尺寸	362*208*35.5 †

端口 5

项目	原稿指标
端口	5
频率范围(MHz)	2300-2400
插入损耗(dB)	≤2.5
带内波动（dB)	≤2.2
带外抑制（dB)	90@1710-1785 90@2500-2570 90@1805-1880 90@3300-3800 90@2110-2170 90@1920-1980 90@2620-2690 60@2412-2485
平均功率容量(W)	≥100W
工作温度(℃)	-30～+60 †
工作湿度（%)	5～95 †
接口形式	DIN/ SMA-F †
外观	黑色油漆 †
外形尺寸	362*208*35.5 †

端口 6

项目	原稿指标
端口	(6,7)
频率范围(MHz)	2496-2690
插入损耗(dB)	≤2.0
带内波动（dB)	≤1.8
带外抑制（dB)	90@1710-1785 90@1805-1880 90@3300-3800 90@2110-2170 90@2300-2400 90@1920-1980
平均功率容量(W)	≥100W
工作温度(℃)	-30～+60 †
工作湿度（%)	5～95 †
接口形式	DIN/ SMA-F †
外观	黑色油漆 †
外形尺寸	362*208*35.5 †

端口 7

项目	原稿指标
端口	8
频率范围(MHz)	3300-3800
插入损耗(dB)	≤2.0
带内波动（dB)	≤1.8
带外抑制（dB)	90@1710-1785 90@2500-2570 90@1805-1880 90@2110-2170 90@2300-2400 90@2620-2690
平均功率容量(W)	≥100W †

工作温度(℃)	-30～+60 †
工作湿度（%）	5～95 †
接口形式	DIN/ SMA-F †
外观	黑色油漆 †
外形尺寸	362*208*35.5 †

说明

· 来源文件：修改-8改7频合路器技术规格书（B1、B3、B40、B41、N78）2.doc
· 特性阻抗：原稿写了 50 Ω 的，以原稿为准；原稿没写的，N 与 SMA 口按 50 Ω。
· 室内型铝合金腔体。测试条件 25 ℃、50 Ω、矢量网络分析仪。出货附该件测试报告。
· 原稿没有互调指标。若订单选择低互调档，按 PIM3 ≤ −150 dBc @ 2×43 dBm 测试并写入报告。
· 多端口表：插损、抑制、隔离只印该端口原稿里有的格子。标 † 的是合并单元格，字只出现在部分端口，已抄到空白端口，数字未改。

English

Factory specification

KXT-FF-28 · 修改-8改7频合路器技术规格书（B1、B3、B40、B41、N78）2

Transcribed from the factory Word file. A column is omitted only when it duplicates the previous column in every row. Typos named in the notes are corrected. Every other number is unchanged.

Port 1

Item	As written
端口	1
频率范围(MHz) / Frequency	1710-1785
插入损耗(dB) / Insertion loss	≤3.0
驻波比 / VSWR	≤1.3
带内波动（dB） / Ripple	≤2.5
带外抑制（dB） / Rejection	90@3300-3800 90@2500-2570 90@1805-1880 90@1920-1980 90@2110-2170 90@2300-2400 90@2620-2690
平均功率容量(W) / Average power	≥100W †
工作温度(℃) / Operating temperature	-30～+60
工作湿度（%） / Humidity	5～95
接口形式 / Connector	DIN/ SMA-F
外观 / Finish	黑色油漆
外形尺寸 / Outline	362*208*35.5

Port 2

Item	As written
端口	2
频率范围(MHz) / Frequency	1805-1880
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8
带外抑制（dB） / Rejection	90@3300-3800 90@1710-1785 90@2500-2570 90@1920-1980 90@2110-2170 90@2300-2400 90@22620-2690
平均功率容量(W) / Average power	≥100W
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	DIN/ SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	362*208*35.5 †

Port 3

Item	As written
端口	3
频率范围(MHz) / Frequency	1920-1980
插入损耗(dB) / Insertion loss	≤3.0
带内波动（dB） / Ripple	≤2.5
带外抑制（dB） / Rejection	90@1710-1785 90@2500-2570 90@1805-1880 90@3300-3800 90@2110-2170 90@2300-2400 90@2620-2690
平均功率容量(W) / Average power	≥100W †
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	DIN/ SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	362*208*35.5 †

Port 4

Item	As written
端口	4
频率范围(MHz) / Frequency	2110-2170
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8
带外抑制（dB） / Rejection	90@1710-1785 90@2500-2570 90@1805-1880 90@3300-3800 90@1920-1980 90@2300-2400 90@2620-2690
平均功率容量(W) / Average power	≥100W
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	DIN/ SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	362*208*35.5 †

Port 5

Item	As written
端口	5
频率范围(MHz) / Frequency	2300-2400
插入损耗(dB) / Insertion loss	≤2.5
带内波动（dB） / Ripple	≤2.2
带外抑制（dB） / Rejection	90@1710-1785 90@2500-2570 90@1805-1880 90@3300-3800 90@2110-2170 90@1920-1980 90@2620-2690 60@2412-2485
平均功率容量(W) / Average power	≥100W
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	DIN/ SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	362*208*35.5 †

Port 6

Item	As written
端口	(6,7)
频率范围(MHz) / Frequency	2496-2690
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8
带外抑制（dB） / Rejection	90@1710-1785 90@1805-1880 90@3300-3800 90@2110-2170 90@2300-2400 90@1920-1980
平均功率容量(W) / Average power	≥100W
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	DIN/ SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	362*208*35.5 †

Port 7

Item	As written
端口	8
频率范围(MHz) / Frequency	3300-3800
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8

带外抑制（dB） / Rejection	90@1710-1785 90@2500-2570 90@1805-1880 90@2110-2170 90@2300-2400 90@2620-2690
平均功率容量(W) / Average power	≥100W †
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	DIN/ SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	362*208*35.5 †

Notes

· Source file: 修改-8改7频合路器技术规格书（B1、B3、B40、B41、N78）2.doc
· Impedance: where the source states 50 Ω, that stands. Where it is silent, N and SMA ports are 50 Ω.
· Indoor aluminum cavity. Tested at 25 °C in a 50 Ω system on a vector network analyzer. A test report ships with the unit.
· The source sheet has no PIM limit. If the order selects the low-PIM option, test PIM3 to ≤ −150 dBc @ 2×43 dBm and put it on the report.
· Multi-port sheet: insertion loss, rejection and isolation are printed only where that port’ s source cell has text. A cell marked † repeats a merged source cell onto a blank port. The number is unchanged.